900XP 400mm Electric Fry Top, Ribbed Brushed Chrome Plate

Modular Cooking Range Line 900XP 400mm Electric Fry Top, **Ribbed Brushed Chrome Plate**

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		
AIA #		



391395 (E9IILIAOMCA)

Half module electric fry top with ribbed brushed chrome cooking plate, sloped, 230V, thermostatic control, scraper included

Short Form Specification

Item No.

Ribbed cooking surface in brushed chrome. Temperature range from 120°C to 280°C. To be installed on open base installations, bridging supports or cantilever systems. Removable drawer below the cooking surface for the collection of grease and fat. Body and work top of unit entirely in stainless steel with Scotch Brite finish. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- Large drain hole on cooking surface permits the draining of fat into large 1 liter collector placed under the cooking surface.
- Electric elements in incoloy positioned under the cooking plate.
- Safety thermostat and thermostatic control.
- Stainless steel high splash guards on the rear and sides of cooking surface. Splash guards can be easily removed for cleaning and are dishwasher-safe.
- Temperature range from 120° up to 280°C.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Rough brushed chrome surface is highly resistant to scratches and facilitates cleaning operations at the end of the day.
- Scraper for ribbed plate included as standard.

Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Cooking surface 15mm thick brushed chrome for optimum grilling results and ease of use.
- Cooking surface completely ribbed.

Included Accessories

• 1 of Scraper for ribbed plate fry **PNC** tops - kit includes knife blades 206420 for both smooth and ribbed surface

Optional Accessories

 Junction sealing kit 	PNC
	206086 🗆
 Support for bridge type 	PNC
installation, 800mm	206137 🗖
 Support for bridge type 	PNC
installation, 1000mm	206138 🗖
 Support for bridge type 	PNC
installation, 1200mm	206139 🗖
 Support for bridge type 	PNC
installation, 1400mm	206140 🗖
 Support for bridge type 	PNC
installation, 1600mm	206141 🗖

APPROVAL:






Modular Cooking Range Line 900XP 400mm Electric Fry Top, Ribbed Brushed Chrome Plate


Water drain for half module fry tops	PNC	206153
• Support for bridge type installation, 400mm	PNC	206154
Back handrail 800mm, Marine	PNC	206308
Back handrail 1200mm, Marine	PNC	206309
 Grease/oil kit container for 700 line frytops (half and module) and 900 line frytops (module) 	PNC 2063	46 🗖
 Chimney grid net, 400mm (700XP/900) 	PNC	206400
 Scraper for ribbed plate fry tops - kit includes knife blades for both smooth and ribbed surface 	PNC	206420
 Side handrail-right/left hand (900XP) 	PNC	216044
• Frontal handrail, 400mm	PNC	216046
• Frontal handrail, 800mm	PNC	216047
• Frontal handrail, 1200mm	PNC	216049
• Frontal handrail, 1600mm	PNC	216050
 Large handrail - portioning shelf, 400mm 	PNC	216185
 Large handrail - portioning shelf, 800mm 	PNC	216186
 2 side covering panels for top appliances 	PNC	216278






Modular Cooking Range Line 900XP 400mm Electric Fry Top, Ribbed Brushed Chrome Plate





Electrical inlet (power) **Equipotential screw**



Electric

Supply voltage:

391395 (E911LIAOMCA) 230 V/3 ph/50/60 Hz

Total Watts: 7.5 kW

Key Information:

Cooking surface width: 330 mm Cooking surface depth: 700 mm 120 °C Working Temperature MIN: 280 °C Working Temperature MAX: Net weight: 55 kg Shipping weight: 65 kg Shipping height: 540 mm Shipping width: 460 mm Shipping depth: 1020 mm 0.25 m³ Shipping volume:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

